NSN 5306-00-886-2999

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-886-2999 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.789 inches and 0.856 inches **Fastener Length:** Between 1.289 inches and 1.356 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.344 inches and 0.406 inches **Head Height:** Between 0.300 inches and 0.305 inches **First Diameter From Head:** Between 0.247 inches and 0.249 inches **Second Diameter From Head:** Between 0.178 inches and 0.183 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.094 inches and 0.156 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 4140 or steel comp 5140 or steel comp 8640 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5306-00-886-2999

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0