

View Online at <https://aerobasegroup.com/nsn/5306-00-887-4324>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.660 inches and 0.810 inches

Fastener Length:

Between 6.810 inches and 6.870 inches

Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

Width Between Flats:

Between 0.640 inches and 0.660 inches

Shoulder Diameter:

0.495 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

6.060 inches first shoulder and 6.090 inches first shoulder

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-b-6812 military specification all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.