

View Online at <https://aerobasegroup.com/nsn/5306-00-890-0938>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

2.139 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.812 inches

**Head Height:**

0.063 inches

**Width Between Flats:**

Between 0.615 inches and 0.625 inches

**Shoulder Diameter:**

Between 0.5601 inches and 0.5606 inches

**Shoulder Length:**

1.764 inches

**Shank Unthreaded Hole Diameter:**

0.108 inches first hole and 0.113 inches first hole

**Concentric Hole Diameter:**

Between 0.195 inches and 0.201 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.064 inches first hole

**Material:**

Steel

**Material Specification:**

G-1013 comp d6ac, fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0