Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-890-0938

| View Online at https://aerobasegroup.com/nsn/5306-00-890-0938 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.375 inches |
| Fastener Length: |
| 2.139 inches |
| Head Style: |
| Round w/wrench flats |
| Head Diameter: |
| 0.812 inches |
| Head Height: |
| 0.063 inches |
| Width Between Flats: |
| Between 0.615 inches and 0.625 inches |
| Shoulder Diameter: |
| Between 0.5601 inches and 0.5606 inches |
| Shoulder Length: |
| 1.764 inches |
| Shank Unthreaded Hole Diameter: |
| 0.108 inches first hole and 0.113 inches first hole |
| Concentric Hole Diameter: |
| Between 0.195 inches and 0.201 inches |
| Thread Diameter: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.064 inches first hole |
| Material: |
| Steel |
| Material Specification: |
| G-1013 comp d6ac, fscm 26512 mfr ref single material response |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Concentric hole unthreaded |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| |

Internally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0