

View Online at <https://aerobasegroup.com/nsn/5306-00-890-0981>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.610 inches

Fastener Length:

Between 1.938 inches and 1.943 inches

Head Style:

Round w/wrench flats

Head Diameter:

0.835 inches

Head Height:

Between 0.140 inches and 0.150 inches

Width Between Flats:

0.750 inches

Shoulder Diameter:

0.4925 inches first shoulder and 0.4936 inches first shoulder

Shoulder Length:

1.328 inches first shoulder and 1.333 inches first shoulder

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.741 inches first hole and 1.746 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

G-1010, fscm 26512 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 2 cl 1 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.