

View Online at <https://aerobasegroup.com/nsn/5306-00-891-3222>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.420 inches and 0.500 inches

**Eye Inside Diameter:**

Between 0.190 inches and 0.196 inches

**Shoulder Thickness:**

Between 0.060 inches and 0.070 inches

**Shank Length:**

Between 0.750 inches and 0.810 inches

**Eye Offset:**

Between 0.760 inches and 0.820 inches

**Overall Length:**

Between 1.460 inches and 1.640 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Center Of Eye To Shank End:**

1.300 inches

**Material:**

Stainless steel

**Material Specification:**

Ams 5355 assn standard single material response or ams 5643 assn standard single material response or mil-s-5059 military specification single material response

**Style Designator:**

Offset, round w/shoulder

**Test Data Document:**

97499-abps4089 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.