## NSN 5306-00-891-8440



Internally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-891-8440 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.979 inches and 0.980 inches **Fastener Length:** Between 1.173 inches and 1.188 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.344 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Hole Diameter:** 0.070 inches **Concentric Hole Depth:** 2.300 inches **Counterbore Diameter:** Between 0.405 inches and 0.412 inches **Concentric Hole Diameter:** Between 0.405 inches and 0.412 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Hole Configuration Style:** Hexagon longitudinal hole Material: Steel **Material Specification:** Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single material response or ams 6300 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Style Designator:** 

N/a

Unf

Shelf Life:

Counterbore unthreaded

Thread Series Designator:

## NSN 5306-00-891-8440

Internally Relieved Body Bolt - Page 2 of 2



H	nit	Ωf	M	eas	ur	Δ.
v		. 0	1414	-u3	uı	С.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.