## NSN 5306-00-893-1694

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-893-1694 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.435 inches **Fastener Length:** Between 3.190 inches and 3.210 inches **Head Style:** Round w/wrench flats chamfered **Head Diameter:** 1.000 inches **Head Height:** Between 0.240 inches and 0.260 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Shoulder Diameter:** 0.6230 inches first shoulder and 0.6235 inches first shoulder **Shoulder Length:** 2.760 inches first shoulder and 2.770 inches first shoulder **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 150000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp 4340 or steel comp e4340 **Material Specification:** Mil-s-5000 military specification all material responses **Surface Treatment:** Nickel and cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5306-00-893-1694

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.