NSN 5306-00-894-2539

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-894-2539

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.765 inches and 0.834 inches |
| Fastener Length: |
| Between 2.781 inches and 2.828 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.359 inches and 0.391 inches |
| Width Between Flats: |
| Between 0.741 inches and 0.751 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 1.984 inches and 2.016 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator: |
| |

Unc

NSN 5306-00-894-2539

Machine Bolt - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0