NSN 5306-00-896-3128

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-896-3128

Thread Direction: Right-hand Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads Thread Diameter:
Right-hand Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads
Locking Feature: Patch threads or strip threads
Patch threads or strip threads
Throad Diameter
Tillead Diameter.
0.190 inches
Grip Length:
Between 0.065 inches and 0.125 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Material:
Steel comp 301 or stainless steel
Material Specification:
66 federal standard single material response or ams5735 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mp-22, fscm 21804 mfr ref single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-00-896-3128

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0