## NSN 5306-00-896-3128

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-896-3128

Thread Direction: Right-hand Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads Thread Diameter:						
Right-hand Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
Thread Length: 0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
0.563 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
Fastener Length: Between 0.735 inches and 0.765 inches  Head Style: Double hexagon extended washer  Head Height: 0.260 inches  Width Between Flats: 0.250 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Locking Feature: Patch threads or strip threads						
Between 0.735 inches and 0.765 inches  Head Style:  Double hexagon extended washer  Head Height: 0.260 inches  Width Between Flats: 0.250 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
Head Style: Double hexagon extended washer Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
Double hexagon extended washer  Head Height: 0.260 inches  Width Between Flats: 0.250 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Locking Feature: Patch threads or strip threads						
Head Height: 0.260 inches Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
0.260 inches  Width Between Flats: 0.250 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Locking Feature: Patch threads or strip threads						
Width Between Flats: 0.250 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Locking Feature: Patch threads or strip threads						
0.250 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
Extended Washer Diameter:  0.375 inches  Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
0.375 inches  Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
Between 0.040 inches and 0.050 inches  Locking Feature:  Patch threads or strip threads						
Locking Feature: Patch threads or strip threads						
Patch threads or strip threads						
Throad Diameter						
Tillead Diameter.						
0.190 inches						
Grip Length:						
Between 0.065 inches and 0.125 inches						
Features Provided:						
Finished head						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
180000 pounds per square inch						
Material:						
Steel comp 301 or stainless steel						
Material Specification:						
66 federal standard single material response or ams5735 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Mp-22, fscm 21804 mfr ref single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						
N/a						

## NSN 5306-00-896-3128

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0