

View Online at <https://aerobasegroup.com/nsn/5306-00-898-9580>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.717 inches

Fastener Length:

3.780 inches

Head Style:

Double hexagon

Head Height:

0.350 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

3.062 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.575 inches first hole

Product Name:

Navy special project

Material:

Steel

Material Specification:

Sps-m-107, fscm 03680 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837 type 1 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.