NSN 5306-00-899-1464

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-899-1464

view Online at https://aerobasegroup.com/nsn/5306-00-899-1464
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.663 inches
Fastener Length:
0.913 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.235 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Hole Diameter:
0.062 inches
Thread Diameter:
0.375 inches
Grip Length:
0.250 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Hole Configuration Style:
Double hexagon flats
Material:
Iron alloy 660
Material Specification:
Ams5732 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

NSN 5306-00-899-1464

Machine Bolt - Page 2 of 2



Specification Data:

80205-nas1006 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.