NSN 5306-00-899-1464



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-899-1464 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.663 inches **Fastener Length:** 0.913 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Hole Diameter:** 0.062 inches **Thread Diameter:** 0.375 inches **Grip Length:** 0.250 inches **Hole Quantity:** 6 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch **Hole Configuration Style:** Double hexagon flats Material: Iron alloy 660

Material Specification:

Ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

NSN 5306-00-899-1464

Machine Bolt - Page 2 of 2



Spe	CITIC	atio	ט חי	ata:

80205-nas1006 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.