View Online at https://aerobasegroup.com/nsn/5306-00-899-9734

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.640 inches

Eye Inside Diameter:

Between 0.375 inches and 0.378 inches

Shoulder Thickness:

Between 0.078 inches and 0.110 inches

Shank Length:

1.843 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

Between 0.7340 inches and 0.7660 inches

Overall Length:

2.844 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Center Of Eye To Shank End:

Between 2.462 inches and 2.474 inches

Eye Outside Width:

Between 0.734 inches and 0.766 inches

Material:

Steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-6758 military specification 1st material response or ams 6300 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.