NSN 5306-00-900-5284

View Online at https://aerobasegroup.com/nsn/5306-00-900-5284

Shear Bolt - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.535 inches and 0.585 inches **Fastener Length:** Between 1.045 inches and 1.075 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Hole Diameter:** 0.050 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.490 inches and 0.510 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon flats Material: Steel **Material Specification:** Sps-m-107, standard pressed steel co mfr ref single material response **Surface Treatment:** Cadmium

NSN 5306-00-900-5284

Shear Bolt - Page 2 of 2



Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0