## NSN 5306-00-900-5284

Shear Bolt - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-00-900-5284

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.535 inches and 0.585 inches
Fastener Length:
Between 1.045 inches and 1.075 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Hole Diameter:
0.050 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
4
Ноlе Туре:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon flats
Material:
Steel
Material Specification:
Sps-m-107, standard pressed steel co mfr ref single material response
Surface Treatment:
Cadmium

## NSN 5306-00-900-5284

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0