

View Online at <https://aerobasegroup.com/nsn/5306-00-900-8697>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.270 inches and 0.330 inches

Fastener Length:

Between 1.090 inches and 1.110 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shoulder Diameter:

0.374 inches first shoulder and 0.375 inches first shoulder

Shoulder Length:

0.690 inches first shoulder and 0.710 inches first shoulder

Hole Diameter:

0.075 inches

Thread Diameter:

0.312 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Hexagon corners

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.