

View Online at <https://aerobasegroup.com/nsn/5306-00-901-4319>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.466 inches

Fastener Length:

1.466 inches

Head Style:

Double hexagon

Head Height:

0.257 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

End Application:

Aircraft, hawkkeye e-2c; aircraft, c-2a (reprocured); aircraft, tomcat f-14

Thread Diameter:

0.438 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas 672 assn standard 1st treatment response or mil-c-8837, type 2 class 1 military specification 2nd treatment response

Thread Series Designator:

Unjf

Specification Data:

26512-gb511b manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.