NSN 5306-00-901-4319

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-901-4319

Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
0.466 inches				
Fastener Length:				
1.466 inches				
Head Style:				
Double hexagon				
Head Height:				
0.257 inches				
Width Between Flats:				
Between 0.678 inches and 0.689 inches				
Grip Diameter:				
Between 0.4358 inches and 0.4367 inches				
End Application:				
Aircraft, hawkeye e-2c; aircraft, c-2a (reprocured); aircraft, tomcat f-14				
Thread Diameter:				
0.438 inches				
Grip Length:				
Between 0.990 inches and 1.010 inches				
Thready Qty Per Inch (tpi):				
20				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Hardness Rating:				
46.0 rockwell c and 50.0 rockwell c				
Material:				
Steel comp h11				
Material Specification:				
Ams6487 assn standard single material response				
Surface Treatment:				
Cadmium or cadmium and chromate				
Surface Treatment Specification:				
Nas 672 assn standard 1st treatment response or mil-c-8837, type 2 class 1 military specification 2nd treatment response				
Thread Series Designator:				
Unjf				
Specification Data:				
26512-gb511b manufacturers standard				
Shelf Life:				

N/a

NSN 5306-00-901-4319

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.