

View Online at <https://aerobasegroup.com/nsn/5306-00-905-2815>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.875 inches

**Fastener Length:**

1.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.544 inches and 0.562 inches

**Shank Unthreaded Hole Diameter:**

0.125 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

0.625 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.344 inches first hole

**Material:**

Steel comp 303 or steel comp 302 or steel comp 304

**Material Specification:**

Stm a582, cond a assn standard single material response or qq-s-763 cond a or c federal specification 2nd material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type

**Departure From Cited Designator:**

As mod by cotter pin hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0