

View Online at <https://aerobasegroup.com/nsn/5306-00-905-8449>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.579 inches

Fastener Length:

2.099 inches

Head Style:

Double hexagon w/hole

Head Height:

0.348 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

0.082 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

End Application:

Helicopter, seahawk, h-60; aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130); helicopter, sof / hh-53h pave low; helicopter, carrier based asw, sh-60f; aircraft, b-2 bomber (atb); advanced cruise missile, acm-129; f117a aircraft; aircraft, phantom f-4; aircraft, hercules c-130; aircraft, galaxy c-5

Thread Diameter:

0.312 inches

Grip Length:

1.500 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 8740 or steel comp e4340 or steel comp 4340 or steel comp 6150 or steel comp 4140

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0