

View Online at <https://aerobasegroup.com/nsn/5306-00-909-5428>

**Thread Class:**

1a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.432 inches and 0.512 inches

**Fastener Length:**

Between 0.990 inches and 1.010 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.271 inches and 0.291 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Hole Diameter:**

0.070 inches

**Shank Unthreaded Hole Diameter:**

0.060 inches first hole

**First Diameter From Head:**

Between 0.276 inches and 0.286 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.310 inches and 0.370 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Hexagon longitudinal hole

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.890 inches first hole and 0.930 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0