## NSN 5306-00-909-5428

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-909-5428 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.432 inches and 0.512 inches **Fastener Length:** Between 0.990 inches and 1.010 inches **Head Style:** Hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Hole Diameter:** 0.070 inches **Shank Unthreaded Hole Diameter:** 0.060 inches first hole **First Diameter From Head:** Between 0.276 inches and 0.286 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.310 inches and 0.370 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** 6 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 **Hole Configuration Style:** Hexagon longitudinal hole Distance From Head Largest Bearing Surface To Shank Hole Center: 0.890 inches first hole and 0.930 inches first hole **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response

Unf

**Thread Series Designator:** 

## NSN 5306-00-909-5428

Externally Relieved Body Bolt - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0