

View Online at <https://aerobasegroup.com/nsn/5306-00-912-4625>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.500 inches

**Fastener Length:**

Between 5.831 inches and 5.855 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.457 inches and 0.481 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Extended Washer Diameter:**

0.938 inches

**Extended Washer Thickness:**

0.125 inches

**First Diameter From Head:**

Between 0.559 inches and 0.565 inches

**Second Diameter From Head:**

Between 0.499 inches and 0.500 inches

**Third Diameter From Head:**

Between 0.433 inches and 0.443 inches

**Fourth Diameter From Head:**

Between 0.499 inches and 0.500 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.375 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.500 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.768 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

4.812 inches

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Externally Relieved Body Diameter Quantity:**

4

**Product Name:**

Navy special project

**Special Features:**

With header point 45 degree by 0.188 in. Lg

**Material:**

Steel

**Material Specification:**

1e60 fscm 11083 mfr ref single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0