

View Online at <https://aerobasegroup.com/nsn/5306-00-912-4625>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

Between 5.831 inches and 5.855 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.457 inches and 0.481 inches

Width Between Flats:

Between 0.736 inches and 0.750 inches

Extended Washer Diameter:

0.938 inches

Extended Washer Thickness:

0.125 inches

First Diameter From Head:

Between 0.559 inches and 0.565 inches

Second Diameter From Head:

Between 0.499 inches and 0.500 inches

Third Diameter From Head:

Between 0.433 inches and 0.443 inches

Fourth Diameter From Head:

Between 0.499 inches and 0.500 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.375 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.500 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.768 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

4.812 inches

Thread Diameter:

0.500 inches

Thread Qty Per Inch (tpi):

20

Externally Relieved Body Diameter Quantity:

4

Product Name:

Navy special project

Special Features:

With header point 45 degree by 0.188 in. Lg

Material:

Steel

Material Specification:

1e60 fscm 11083 mfr ref single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0