## NSN 5306-00-912-5332

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-912-5332 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.394 inches and 0.444 inches **Fastener Length:** Between 0.904 inches and 0.934 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.359 inches and 0.369 inches **Extended Washer Thickness:** 0.040 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 1 cl 2 military specification single treatment response or mil-c-8837, type 2 cl 2 military specification single treatment response **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5306-00-912-5332

Shear Bolt - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.