NSN 5306-00-912-5334

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-912-5334

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.394 inches and 0.444 inches

Fastener Length:

Between 0.966 inches and 0.996 inches

Head Style:

Double hexagon w/hole

Head Height:

0.214 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.359 inches and 0.369 inches

Extended Washer Thickness:

0.040 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 1 cl 2 military specification single treatment response or mil-c-8837, type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-00-912-5334

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

