## NSN 5306-00-914-2809

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-914-2809 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.685 inches **Fastener Length:** 1.500 inches **Head Style:** Hexagon **Head Height:** Between 0.171 inches and 0.205 inches Width Between Flats: Between 0.484 inches and 0.500 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.815 inches and 0.875 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 63.0 microinches Material: Steel comp 8740 or steel comp 4130 or steel comp 4037 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-6758 military specification 2nd material response or ams 6300 assn standard 3rd material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5306-00-914-2809

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.