

View Online at <https://aerobasegroup.com/nsn/5306-00-914-3245>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.518 inches

**Fastener Length:**

2.266 inches

**Head Style:**

Double hexagon

**Head Height:**

0.281 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Grip Diameter:**

Between 0.4982 inches and 0.4991 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

1.750 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.126 inches first hole

**Material:**

Steel

**Material Specification:**

Sps-m-107, fscm 03680 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0