## NSN 5306-00-914-9506

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-914-9506
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.596 inches
Fastener Length:
Between 1.480 inches and 1.500 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.250 inches and 0.270 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
Between 0.040 inches and 0.050 inches
First Diameter From Head:
Between 0.188 inches and 0.189 inches
Second Diameter From Head:
Between 0.137 inches and 0.141 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.783 inches and 0.843 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.894 inches
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
29.0 rockwell c and 42.0 rockwell c
Externally Relieved Body Diameter Quantity:
2
Material:
Iron alloy 660
Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:

N/a

## NSN 5306-00-914-9506

Externally Relieved Body Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0