

View Online at <https://aerobasegroup.com/nsn/5306-00-915-1982>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.562 inches and 0.582 inches

Fastener Length:

Between 5.000 inches and 5.020 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Concentric Hole Diameter:

Between 0.303 inches and 0.323 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.872 inches first hole

Special Features:

Concentric hole filled with epocast 169, furance plastics inc

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0