

View Online at <https://aerobasegroup.com/nsn/5306-00-915-2067>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.731 inches and 0.751 inches

**Fastener Length:**

2.366 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.435 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

**Extended Washer Thickness:**

0.099 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0