## NSN 5306-00-916-4452

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-916-4452

| Inread Class:  |
|--|
| 3a   |
| Thread Direction:                                      |
| Right-hand   |
| Thread Length:   |
| 0.852 inches   |
| Fastener Length:                                       |
| 2.477 inches   |
| Head Style:  |
| Double hexagon   |
| Head Height:   |
| 0.400 inches   |
| Width Between Flats:                                   |
| Between 1.052 inches and 1.064 inches                  |
| Grip Diameter:   |
| Between 0.7480 inches and 0.7490 inches                |
| Thread Diameter:                                       |
| 0.750 inches   |
| Grip Length:   |
| 1.625 inches   |
| Thready Qty Per Inch (tpi):                            |
| 16   |
| Min. Tensile Strength (psi):                           |
| 220000 pounds per square inch                          |
| Hardness Rating:                                       |
| 46.0 rockwell c and 50.0 rockwell c                    |
| Material:  |
| Steel  |
| Material Specification:                                |
| Sps-m-107, fscm 03680 mfr ref single material response |
| Surface Treatment:                                     |
| Cadmium  |
| Surface Treatment Specification:                       |
| Nas 672 assn standard single treatment response        |
| Thread Series Designator:                              |
| Unjf   |
| Specification Data:                                    |
| 56878-ewsb22 manufacturers standard                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |

--

## NSN 5306-00-916-4452

Shear Bolt - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A003b0