

View Online at <https://aerobasegroup.com/nsn/5306-00-916-4465>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.663 inches

**Fastener Length:**

4.788 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 4.110 inches and 4.140 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.553 inches first hole and 4.573 inches first hole

**Special Features:**

Tensile strength at room temperature

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0