## NSN 5306-00-916-4465

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-916-4465

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.663 inches
Fastener Length:
4.788 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.235 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
Between 4.110 inches and 4.140 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
4.553 inches first hole and 4.573 inches first hole
Special Features:
Tensile strength at room temperature
Material:
Iron alloy 660
Material Specification:
Ams5732 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## **NSN 5306-00-916-4465** Machine Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A003b0