## NSN 5306-00-916-6461

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-916-6461 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.632 inches **Fastener Length:** 1.382 inches **Head Style:** Hexagon **Head Height:** 0.188 inches Width Between Flats: Between 0.492 inches and 0.501 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** 0.750 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.109 inches first hole **Special Features:** Tensile strenght at room temperature Material: Iron alloy 660 **Material Specification:** Ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

## **NSN 5306-00-916-6461** Machine Bolt - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

Demilitarization:

No

Fiig:

A003b0