

View Online at <https://aerobasegroup.com/nsn/5306-00-916-6499>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.481 inches

Fastener Length:

2.231 inches

Head Style:

Hexagon

Head Height:

0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

1.750 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.016 inches first hole

Special Features:

Tensile strength at room temperature

Material:

Iron alloy 660 or steel comp 630

Material Specification:

Ams 5735 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.