# NSN 5306-00-917-6258

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-917-6258



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.313 inches and 0.363 inches

#### Fastener Length:

Between 1.448 inches and 1.478 inches

#### Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Grip Diameter:

Between 0.1890 inches and 0.1895 inches

## Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

## **Thread Diameter:**

0.190 inches

## Grip Length:

Between 1.115 inches and 1.135 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Distance From Head Largest Bearing Surface To Shank Hole Center:

1.275 inches first hole and 1.325 inches first hole

## Material:

Titanium alloy uns r54520

## **Material Specification:**

Nas 621, 6al-4v assn standard single material response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas673 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-00-917-6258

Shear Bolt - Page 2 of 2

Fiig: A003b0

