

View Online at <https://aerobasegroup.com/nsn/5306-00-917-6292>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 0.761 inches and 0.796 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.428 inches and 0.448 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.588 inches first hole and 0.638 inches first hole

**Material:**

Titanium alloy uns r54520

**Material Specification:**

Nas 621, 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas673 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0