

View Online at <https://aerobasegroup.com/nsn/5306-00-917-9772>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.514 inches and 0.574 inches

Fastener Length:

Between 1.779 inches and 1.809 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 1.235 inches and 1.265 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.552 inches first hole and 1.572 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1004 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0