NSN 5306-00-918-4808

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-918-4808 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.587 inches and 0.720 inches **Fastener Length:** Between 2.210 inches and 2.230 inches **Head Style:** Dee chamfer **Head Diameter:** Between 0.615 inches and 0.635 inches **Head Height:** Between 0.190 inches and 0.210 inches **Distance From Centerline To Flat:** Between 0.176 inches and 0.186 inches First Diameter From Head: Between 0.378 inches and 0.379 inches **Second Diameter From Head:** Between 0.310 inches and 0.320 inches **Third Diameter From Head:** Between 0.378 inches and 0.379 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.160 inches and 1.180 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 1.510 inches and 1.540 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Ams 5708 assn standard single material response

Nickel alloy **Material Specification: Thread Series Designator:** Unf Shelf Life: N/a

NSN 5306-00-918-4808

Externally Relieved Body Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0