## NSN 5306-00-920-1104

Machine Bolt - Page 1 of 2

**Thread Class:** 





3a **Thread Direction: Right-hand Thread Length:** Between 0.419 inches and 0.439 inches Fastener Length: Between 0.490 inches and 0.510 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches Hole Diameter: 0.062 inches **Thread Diameter:** 0.250 inches Grip Length: 0.071 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 8740 **Material Specification:** 

Ams 6322 assn standard single material response

## NSN 5306-00-920-1104

Machine Bolt - Page 2 of 2



Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0