

View Online at <https://aerobasegroup.com/nsn/5306-00-921-0857>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.492 inches and 0.532 inches

**Fastener Length:**

Between 2.502 inches and 2.522 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.290 inches and 0.310 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.438 inches

**Extended Washer Thickness:**

Between 0.059 inches and 0.079 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.990 inches and 2.010 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.