

View Online at <https://aerobasegroup.com/nsn/5306-00-922-1469>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.293 inches and 0.313 inches

**Fastener Length:**

Between 1.732 inches and 1.737 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.938 inches

**Head Height:**

Between 0.140 inches and 0.150 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Shoulder Diameter:**

0.5601 inches first shoulder and 0.5607 inches first shoulder

**Shoulder Length:**

1.325 inches first shoulder and 1.330 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 49.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.535 inches first hole and 1.540 inches first hole

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Navy special project

**Material:**

Steel

**Material Specification:**

G-1010, fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type 2 cl 1 military specification single treatment response

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.