

View Online at <https://aerobasegroup.com/nsn/5306-00-922-1486>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.387 inches

**Fastener Length:**

2.322 inches

**Head Style:**

Hexagon

**Head Height:**

0.100 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3725 inches and 0.3731 inches

**Shank Unthreaded Hole Diameter:**

0.075 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.935 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

46.0 rockwell c and 49.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.221 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0