

View Online at <https://aerobasegroup.com/nsn/5306-00-922-6433>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.528 inches

**Fastener Length:**

Between 0.710 inches and 0.730 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

0.062 inches

**First Diameter From Head:**

Between 0.249 inches and 0.251 inches

**Second Diameter From Head:**

Between 0.197 inches and 0.201 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.110 inches and 0.130 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.162 inches and 0.202 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Nickel alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0