NSN 5306-00-922-6433

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-922-6433 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.528 inches **Fastener Length:** Between 0.710 inches and 0.730 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.249 inches and 0.251 inches **Second Diameter From Head:** Between 0.197 inches and 0.201 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.162 inches and 0.202 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 2

Material:

Nickel alloy

NSN 5306-00-922-6433

Externally Relieved Body Bolt - Page 2 of 2



	Materia	al Sp	ecific	ation:
--	---------	-------	--------	--------

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0