

View Online at <https://aerobasegroup.com/nsn/5306-00-922-8999>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.530 inches and 0.540 inches

Fastener Length:

Between 1.620 inches and 1.640 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.480 inches and 0.500 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Extended Washer Diameter:

Between 0.678 inches and 0.698 inches

Extended Washer Thickness:

Between 0.110 inches and 0.120 inches

Shoulder Diameter:

0.4350 inches first shoulder and 0.4360 inches first shoulder

Shoulder Length:

1.080 inches first shoulder and 1.090 inches first shoulder

Shank Unthreaded Hole Diameter:

0.094 inches first hole and 0.101 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.472 inches first hole and 1.502 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0