

View Online at <https://aerobasegroup.com/nsn/5306-00-924-1724>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.073 inches and 1.113 inches

**Fastener Length:**

Between 2.178 inches and 2.198 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

0.062 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**First Diameter From Head:**

Between 0.248 inches and 0.249 inches

**Second Diameter From Head:**

Between 0.222 inches and 0.232 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.350 inches and 0.370 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.715 inches and 0.755 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Hexagon longitudinal hole

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.068 inches first hole and 2.088 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0